

POSTSAVER®

Premium Fence Posts preventing premature rot at ground level

Pro-contractor Sleeve Application Machine - Gas Powered



- Applies 50 to 80 sleeves per hour (depending on post size) to timber fence posts (not wet)
- Caters for post size up to 6" round or 5" square
- A press unit is required for square posts

Machine specification

Post size range:	75 to 150mm round, 75 to 125mm square or rectangular
Post length range:	1675 to 3000mm*
Throughput:	up to 100 poles or post per hour (50-80 with single operator)
Machine size floor area:	approx 3.0m x 1.0m (with press)
Machine weight approx:	120 kg
Power requirement:	Bottled propane gas (regulator supplied)
Gas consumption:	Approx. 0.6 kg per hour (approx. 80p)

*longer post lengths can be accommodated with the use of additional supports (not included)

Installation - please note

The machines are supplied in 2 or more parts, some onsite assembly is required. All machines to be installed on level hard standing in a dry and draught/wind free environment, use in very cold environments or with cold/damp posts can reduce throughput. For maximum throughput we recommend the use of scissor lift or support tables to support pallets of posts at height optimum for operator efficiency. Machine set up and use is straightforward and comprehensive instructions are supplied

Payment terms: payment with order

Warranty: 12 months parts

Issued March 2010

Postsaver Europe Ltd, Willow House, School Lane, Upton-on-Severn Worcestershire WR8 0LE, United Kingdom
Tel: 0845 643 4089 Fax: 0845 643 6254 email: sales@postsaver.co.uk www.postsaver.co.uk